



**Specifications Philips LED  
SlimDownlight Coreline DN145C 21W  
2100lm 84D - 840 Cool White | 222mm  
- IP44**

[View Product](#)

## General Information

|                          |                             |
|--------------------------|-----------------------------|
| SKU                      | 235942                      |
| EAN                      | 8710163339542               |
| Brand                    | Philips                     |
| Manufacturer Name        | DN145C LED20S/840 PSU II WH |
| Any Lamp all-in warranty | 5 Years                     |
| Average Lifetime (h)     | 35000                       |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |
| Light colour options        | Single Color      |
| Driver Included             | Yes               |
| Beam Angle (degree)         | 84                |

|                          |                                       |
|--------------------------|---------------------------------------|
| Luminous Efficacy (lm/W) | 100                                   |
| Power factor             | >0.90                                 |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Optical Cover            | PMMA (Polymethyl methacrylate)        |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| EOC8                   | 33954299          |
| Mounting Method        | Surface           |
| Cut out (mm)           | 222               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | 0 to +35          |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Fixture Connection     | Cable, 2-pole     |
| Series                 | DN145C            |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 50  |
| Diameter (mm) | 222 |

## Why Any-lamp?

## Sensor Information


 Order from the **largest lighting specialist** in Europe


**Customised** quotation


 Up to **7 years warranty**


**Easy** return process